
## Rotorflush RUBI 80SFQ21.5-400AR Range Self-cleaning Filterpump

**General Specifications** 

#### **General Arrangements**




#### **Key Features**

- Integral self-cleaning filter
- 316 Stainless steel filter mesh
- Filter mesh from 315 micron 3 mm
- Reliable and low maintenance
- Continuous backwash whenever water is being pumped
- Capital, installation and maintenance costs reduced
- All stainless steel filter cage construction

**General Specifications** 

#### **Performance Curves**



www.rotorflush.com

Tel: +44 (0)1297 560229

Email: sales@rotorflush.com

# Rotorflush RUBI 80SFQ21.5-400AR Range Self-cleaning Filterpump General Specifications

#### **Pump Specification**

#### Specification

Electric submersible pump
Degree of protection IP 68
Depth of submersion Type of impeller Semi-open
Max. solid handling 6 mm
Suitable for:
corrosive liquids

#### **Electric motor**

Dry-type submersible induction motor Insulation class F 2 Poles 2910 Starting mode Directly Rated voltage 400 V 50 Hz Power uptake 2.07 kW Rated power 1.50 kW Rated current 3.8 A Start current 35.0 A

#### Cable

10m H07RN-F 4Cx1,5mm2

#### **Motor Protection**

Miniature protector in windings (snap-action bi-metal device)

#### Shaft seal

Double inside mechanical seal in oil bath additional lubrication by oil lifting device Primary seal
Silicon carbide on silicon carbide
Secondary seal
Silicon carbide on silicon carbide

#### **Bearings**

Shielded ball bearings, maintenance-free

#### **Materials**

ImpellerSCS14 (SUS GX5CrNiMo19-11-2)Pump casingSCS14 (SUS GX5CrNiMo19-11-2)Suction coverSCS14 (SUS GX5CrNiMo19-11-2)Motor FrameSCS14 (SUS GX5CrNiMo19-11-2)ShaftSUS316 (EN-X5CrNiMo17-12-2)

#### Discharge size

80mm JIS10K flange

#### Weight

36 kg (dry weight of the pump only without cable)

# Rotorflush RUBI 80SFQ21.5-400AR Range Self-cleaning Filterpump General Specifications


### **Self-cleaning Filterpump Specification**


Self-cleaning Filter Construction	
Filter Screen Area	2500cm2
Standard Screen Sizes	315 micron, 1mm, 2mm
Filter mesh	316 Sintered stainless steel mesh (315 micron) 316 Stainless steel woven mesh (1mm and 2mm)
Impeller Extension Shaft	Stainless Steel
Impeller	Stainless steel
Rotor	ABS (Acrylonitrile Butadiene Styrene)
Rotor Bearings	Silicon Carbide
Filter Cage	Stainless Steel
Cleaning Jets	Natural Rubber Jets, Stainless Steel Clips


## Rotorflush RUBI 80SFQ21.5-400AR Range Self-cleaning Filterpump

**General Specifications** 

#### **Dimensions**







### Approx weight 60kg

\*Dimensions and weights are approximate